

Sandberg Survivor Powerbank 9in1 144000

Specificaties

Battery capacity: 3.2V/144000 mAh/460.8 Wh
Battery pack capacity: 12.8V/36000 mAh/460.8 Wh
Battery type: LiFePO₄ battery cells
1 x DC input: 12-24V/5A (120W max)
1 x Solar charging input: Up to 100W (MPPT control)
1 x Small Anderson (solar input): 12-24V/8A (MPPT 160W max)
1 x USB-C1 PD input: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W max)
1 x USB-C1 PD output: 5W/3A, 9W/3A, 12V/3A, 15W/3A, 20V/5A (100W max)
1 x USB-C2 PD output: 5W/3A, 9W/2A, 12V/2.25A, PPS 4.4-11V/3A
2 x USB-A QC 3.0 outputs: 5V/3A, 9V/2A, 12V/1.5A (18W max each)
2 x Car Lighter Socket: 12V/15A (180W max)
1 x Big Anderson output: 12V/30A (360W max)
IPX4 water-resistant
Working temperature: 0°C to +40°C
Operating temperature: 0°C to +40°C



Verpakkingsinformatie

1 Sandberg Survivor Powerbank 9in1 144000
1 AC charger, input AC 100-240V output DC 20V/2A 40W, cable length 1m (EU+UK plug)
1 USB-C to USB-C charging cable, 75 cm
1 Carry case
1 Quick guide
1 GPSR Safety guide

Snelle gids: <https://sandberg.world/mt/manual/421-37>

Afmetingen

	Product	Verpakking
Hoogte (cm)	8,10	24,00
Breedte (cm)	22,00	22,00
Diepte (cm)	38,00	8,10
Gewicht (g)	4.500,00	5.530,00



Product:
www.sandberg.world/product/survivor-powerbank-9in1-144000

 **Sandberg®**

Dealer: