Technical Data

GENERAL DATA	
Frequency	[illegible] kHz/59-61 Hz (DisplayPort: 31-89 kHz/59-61 Hz), [illegible] 31-89 kHz/ 49-61 Hz/59-61 Hz
Power consumption (typical) (in watts)	[illegible]
Maximum Power Consumption (in watts)	[illegible] maximum brightness with all signal inputs and [illegible]
Product line	[illegible]
Max. Power consumption in stand-by mode (in watts)	[illegible]
Mode of operation	[illegible] and medium-sized companies, Private user, [illegible]
Power consumption with power switch off (in watts)	[illegible] hospital administration
Specific system requirements	None, [illegible]
Energy efficiency class	Systems including macOS and Win
Energy consumption/1000h (in kWh)	159.5 / 170.5 / 166.38 / 159.0 / 170.5 / 166.46
Power supply	AC 100-120 V / 200-240 V, 50/60 Hz
USB-C Power Delivery (in Watt)	70
Power management	✓
Screen size (in cm)	68.5
DIMENSIONS & WEIGHT	
Panel	[illegible]
Dimensions (incl. stand) (width x height x depth) (in mm)	611 x (349 – 545) x 230
Dimensions (without stand) (width x height) (in mm)	597 x 336
Weight (incl. stand) (in kg)	8.6
Ideal and recommended resolution	2560 x 1440
Dimensions (without stand) (width x height x depth) (in mm)	611 x 367 x 58
Weight (without stand) (in kg)	6.3
Possible mounting	[illegible]
Operating temperature	[illegible]
Resolution (in mm)	[illegible]
Viewing angle (in °)	178 x 178
Pixel pitch (in mm)	0.233
Pixel density (in ppi)	109
Max. brightness (typical) (in cd/m²)	350
Max. dark room contrast (typical)	1000:1
Response time (in ms) (grey-to-grey)	8
Backlight	LED
SUPPLIED ACCESSORIES	
Accompanying software and other accessories available for download	Screen InStyle
Other box contents	USB/signal cable (USB-C - USB-C), Manual via download, Power cord, Quick guide
Accessories	PM200-K, CP200, HD-CBR-K, CC100, PP100-K, PP200-K, PCSK-03

FEATURES & OPERATION	
Tilt/Swivel/Pivot/Height	✓
Power switch	✓
Included warranty	Zero pixel defects guarantee, no fully illuminated sub-pixels allowed, [illegible] years from date of purchase
Preset color/greyscale modes	[illegible]
[illegible]	✓
[illegible] OM tone curve	✓
[illegible]	✓
[illegible]	✓
[illegible]	✓
[illegible]	✓
No [illegible]	✓
HDCP Decoder	✓
Automatic signal input recognition	✓
Built-in speakers	✓
On-screen menu languages	de, en, fr, es, it, ze
Adjustment options	Color Mode, Brightness, Contrast, Color temperature / White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal Input, All EcoView functions, Volume
Button Guide	✓
[illegible]	✓
CONNECTIONS	
LAN/RJ-45	✓
Signal inputs	USB-C (DisplayPort Alt Mode, HDCP 1.3), DisplayPort (HDCP 1.3), HDMI (HDCP 1.4)
Signal outputs	USB-C (for daisy chain)
Daisy-chain capable	✓
USB specification	USB 5 Gbps (USB 3)
USB upstream ports	1 x type C (DisplayPort Alt Mode, 70 W max.), 1 x type B
USB downstream ports	3 x type A, 1 x type C (DisplayPort Alt Mode, 15 W max.)
Network connection	RJ-45
[illegible]	[illegible]
Graphic signal	USB-C, DisplayPort, HDMI (RGB, YUV)
Audio signal	[illegible]
Audio / headphone output	3.5 mm stereo jack

→ Product Website → Experience in AR

Experience the EV2795 in AR now!

Thanks to its USB-C ports and USB-C daisy chain functionality, the EV2795 ensures that there are fewer cables and more freedom on the desk. Its virtually frameless design also makes it shine. This impressive monitor boasts unparalleled image quality, ergonomics and a range of modern connection options, meaning it is perfectly suited to satisfy your requirements for the office and for at home. Laptop and tablet users will be impressed by the monitor's fully functional docking station, which includes a LAN connection and charging port for the computer. Dual-screen systems can be set up easily using USB-C daisy chain. The two USB upstream ports allow the EV2795 to be used as a keyboard/mouse switch. For example, if both a private PC and company computer are connected to the monitor in your home office, both computers can be operated with a single keyboard and mouse and with anu other chained monitors.

- 27-inch IPS Monitor with 2560 x 1440 pixels and fine resolution of 109 ppi
- Auto EcoView, EcoView index and EcoView Optimizer for maximum power savings and superb ergonomics
- Docking functionality for tablets, laptops and smartphones thanks to USB 3.1 Type-C connectivity supplying a LAN and power charging of 70 watts
- USB-C daisy chain functionality (USB-C output) for connecting another monitor
- Signal inputs: USB-C (DisplayPort Alt Mode), Display Port, HDMI
- Elegant design: Frame amazingly compact and ultra-sleek
- 1000:1 contrast ratio, brightness: 350 cd/m², 178° viewing angle
- Production that is proven to be environmentally friendly and socially responsible
- 5-year warranty for highest investment security

Find your EIZO contact
EIZO Europe GmbH
Belgrader Straße 2
41069 Mönchengladbach
Phone: +49 2161 8210 0
www.eizo.eu

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 15.07.2024