

Sandberg Travel Charger PD100W Display

Caractéristiques

World adapter plugs included: EU, UK, Australia (US plug built in)
Input: AC 100-240V 50/60Hz 1.5A Max
Output:
USB-C1: 5W/3A, 9W/3A, 12V/3A, 15W/3A, 20V/5A, PPS: 3.3-21V/5A (100W Max)
USB-C2: 5W/3A, 9W/3A, 12V/3A, 15W/3A, 20V/5A, PPS: 3.3-21V/5A (100W Max)
USB-A: 5V/3A, 9V/2A, 12W/1.5A (18W Max)
USB-C1+USB-C2: 65W+35W (100W Max)
USB-C1/C2+USB-A: 65W+18W (83W Max)
USB-C1+USB-C2+USB-A: 45W+35W+18W (98W Max)
Total output: 100W Max
V0 fire-proof PC housing
GaN charger
Digital display showing charging power, temperature, usage time and power distribution



Infos sur l'emballage

1 Sandberg Travel Charger PD100W Display
1 EU plug
1 UK plug
1 AUS plug
1 Carry pouch
1 GPSR Safety guide

Guide rapide: <https://sandberg.world/en/manual/441-71>

Dimensions

	Produit	Conditionnement
Hauteur (cm)	6,90	15,00
Largeur (cm)	6,90	12,00
Profondeur (cm)	3,30	5,00
Poids (g)	245,00	310,00

 Sandberg®



Produit:
www.sandberg.world/product/travel-charger-pd100w-display

Revendeur: