Technical Data

DIMENSIONS & WEIGHT

Dimensions (incl. stand) (width x height x depth) (in mm)	522 x 390 x 188,3 x 233 EV2410-BAT
Weight (incl. stand) (in kg)	Black White
Dimensions (without stand) (width x height x depth) (in mm)	522 x 345,2 x 57 Other
Weight (without stand) (in kg)	FlexScan
Dimensions drawing (PDF)	Dimensional drawing (EV2410-BAT, EV2410-WHT, EV2410-BK)
Rotatability of the stand (in °)	344
Specific system requirements	
Tiltability forwards/backwards (in °)	-5 to 35
Pivot: between portrait / landscape	90° (CW) or 270° (CCW) 90° clockwise or 90° counter-clockwise
Height adjustment range (in mm)	129,9

SCREEN

Pixel pitching	100 x 100
Screen size (in inches)	24,1
Screen size (in cm)	61,1
Format	16:10
Viewable image size (width x height)	518,4 x 324 mm
Brightness	350 cd/m²
Contrast	1300:1
Native and recommended resolution	1920 x 1200
Pixel pitch (in mm)	0,27 x 0,27
Viewing angle (in °)	178
Response time grey-grey (in ms)	5
Colours displayable	16,7 million
Supported resolutions for down-scaling	1920 x 1200, 1920 x 1080 (Full HD), 1280 x 1024, 1600 x 1200, 1440 x 900, 1280 x 960, 1280 x 800, 1024 x 768, 800 x 600, 640 x 480
Other box contents	USB cable (Type A - Type B), Signal cable DisplayPort (1.8 m), Power cord, Getting Started guide
Accessories	PM200-K (DisplayPort cable to transfer digital video and audio signals), HD200B-K (HDMI High Definition Multimedia cable), HD200B-K (HDMI High Definition Multimedia cable), DC5-K
Number of colors or greyscale	16,7 million colors (DisplayPort, 8 Bit), 16,7 million colors (HDMI, 8 Bit)

WARRANTY

Warranty period	7 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
Max. operating hours	30000
Max. brightness (typical) (in cd/m²)	350
Max. darkroom contrast (typical)	1300:1

FEATURES & OPERATION

Preset color/greyscale modes	2x manual memory locations, sRGB, Paper, Movie, DICOM
DICOM tone curve	✓
Auto EcoView	✓
EcoView Index	✓
EcoView Optimizer	✓
Overdrive	✓
No flickering	✓
HDCP Decoder	✓
Automatic signal input recognition	✓
Built-in speakers	✓ (2 Watt / 1 + 1 Watt)
On-screen menu languages	de, en, fr, es, it, ja
Adjustment options	Color Mode, Brightness, Contrast, Color temperature, Gamma, Sharpness, Hue, Color saturation, Resolution, Scaling, Menu Rotation, Monitor reset, OSD language, Signal input, All EcoView functions, Volume, Key lock
Button Guide	✓
Integrated power unit	✓

CONNECTIVITY

Signal input	DisplayPort (version 1.1a), HDMI (version 1.4), D-Sub
USB hub	USB 3.2 Gen 1 (5 Gbps)
Digital signal	DVI single-link (HDCP), HDMI (HDCP), DisplayPort (HDCP)
Graphic signal	DVI single-link (HDCP), HDMI (HDCP), DisplayPort (RGB, YUV)
Sync formats	Separate
Audio input	3.5 mm stereo jack, DisplayPort, HDMI
Audio / headphone output	3.5 mm stereo jack

ELECTRICAL DATA

Frequency	DisplayPort: 31-76 kHz / 59-61 Hz; HDMI: 31-76 kHz / 59-61 Hz; DVI-D: 31-76 kHz / 59-61 Hz; D-Sub: 31-81 kHz / 55-76 Hz
Power consumption (typical) (in watts)	8
Maximum Power Consumption (in watts)	54 (at maximum brightness with all signal inputs and USB ports in use)
Max. Power consumption in stand-by mode (in watts)	0,5
Power consumption with power switch off (in watts)	0
Energy efficiency class	B
Energy consumption/1000h (in kWh)	8
Power supply	AC 100-240V, 50/60Hz
Power Management	✓

CERTIFICATION & STANDARDS

Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified generation 10, TÜV/Low Blue Light Content, TÜV/Flicker Free, RCM, cTÜVus, EAC, KCC, VCCI-B, PSE, BSMI, J-MOSS (JIS C 6950-1), TÜV/S, WEEE, China RoHS, CCC
Format	EPEAT Gold (US), EPEAT Climate+

SOFTWARE & SERVICES

Shading in ppt	64
Accompanying software and other	ScreenManager Pro for Windows, ScreenManager Pro for Mac, ColorNavigator 7

OTHER

Cabinet color	Black
Power cord	Detachable
Tilt	Yes
Swivel	Yes
Pivot	Yes
Height adjustable stand	Yes
Kensington lock	Yes
Wall mount interface	100 x 100 mm

24" office monitor

The FlexScan EV2410R impresses as a flexible all-rounder and is ideal for the classic office workstation. Energy-saving, eye-friendly and ergonomic, it is an indispensable helper on any desk and enables efficient working. Equipped with an IPS panel, it has a horizontal and vertical viewing angle of 178° and a resolution of 1920 x 1200 pixels. The low-reflection surface, brightness and contrast ensure a detailed and excellent image reproduction. Auto EcoView automatically adjusts the brightness to the ambient light to avoid glare and protect the eyes. Four inputs for digital and analog signals, a USB hub and headphone and audio connectivity. Thanks to the thin housing edge, the monitor has a very compact appearance and is particularly suitable for multi-screen operation. In addition to the on-screen menu, the accompanying ScreenManager software enables easy operation via computer or network.

- 24" office monitor in 16:10 format with ergonomic and space-saving design
- DisplayPort, HDMI, DVI-D and D-Sub inputs for digital and analog connection
- Auto EcoView Index and EcoView Optimizer
- Ergonomic stand for optimum ergonomics
- 5 Gbps USB hub with one upstream and four downstream ports
- Environmentally conscious and socially responsible production
- Optionally in black or white housing color
- 7-year warranty for maximum investment security

Experience the EV2410R in AR now!

→ Product Website → Experience in AR

Find your EIZO contact
EIZO Europe GmbH
Belgrader Straße 2
41069 Mönchengladbach
Phone: +49 2161 8210 0
www.eizo.eu

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies.
Copyright © 2026 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany.
All rights, errors and modifications reserved. Latest update: 25.05.2026