Technical Data

CERTIFICATION & STANDARDS

Certification	CE, cULus, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), EPEAT Certified Generation 3, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker free, RCM, cULus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, UL ENERGY STAR, RoHS, WEEE, China RoHS, CCC, BIS, ISMI, EAC
Areas of application	Office

SOFTWARE & ACCESSORIES

Accompanying software and other accessories available for download	ScreenStyle Large and medium-sized companies, Private user & small business, Finance
Scope of delivery	[illegible], Quick guide
EAN	4995047048198
Accessories	[illegible], HD2001PR-K, PC

WARRANTY

Warranty (in years)	5 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
Included warranty	Zero pixel defects guarantee, no fully illuminated sub-pixels (sub-pixels ISO 9241-307) for six months from date of purchase.

DISPLAY

Viewable image size (width x height) (in mm)	488.2 x 297.2
Ideal resolution	1920 x 1200
Pixel pitch	0.254 x 0.254
Pixel density	[illegible]
Supported resolutions	[illegible] x 1200, 1600 x 1200, 1280 x [illegible]
Panel technology	[illegible]
Max. viewing angle horizontal	178
Max. viewing angle vertical	178
Number of colors or greyscale	16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DVI, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit)
Color palette look-up table	[illegible] colors / 14 bit
Max. color space (typical)	sRGB
Max. brightness (typical) (in cd/m²)	[illegible]
Max. dark room contrast (typical)	1000:1
Response time, gray-to-gray (typical) (in ms)	[illegible]
Backlight	LED

CONNECTIONS

Signal inputs	D-Sub, DisplayPort (HDCP 1.3), HDMI (HDCP 1.4)
USB specification	USB 5Gbps (USB 3)
USB upstream ports	1 x type B
USB downstream ports	2x type A
Graphic signal	RGB Analog, DisplayPort, HDMI (RGB, YUV)
Sync formats	Separate
Audio input	3.5 mm stereo jack, DisplayPort, HDMI
Audio / headphone output	3.5 mm stereo jack

Find your EIZO contact
EIZO Europe GmbH
Belgrader Straße 2
Phone: +49 2161 8210-0
www.eizo.eu

FEATURES & OPERATION

Preset color/grayscale modes	2 x manual memory locations, sRGB, Paper, Movie, DICOM
DICOM tone curve	✓
Auto EcoView	✓
EcoView Index	✓
EcoView Optimizer	✓
Overdrive	✓
No flicker ing	✓
HDCP Decoder	✓
Automatic signal input recognition	✓
Built-in speakers	✓
On-screen menu languages	de, en, Fr, es, It, ze
Adjustment options	Color Mode, Brightness, Contrast, Color temperature [illegible], Gamma, [illegible], Sharpness, Color saturation, Resolution, Scaling, OSD language, Signal Input, All EcoView functions, Volume
Button Guide	✓
Integrated power unit	✓

→ Product Website → Experience in AR

ELECTRICAL DATA

Frequency	DisplayPort: 31.744 kHz–89.81 Hz; HDMI: 15–75.5 kHz / [illegible] Hz; D-Sub: 31.744 kHz–89.81 Hz
Power consumption (typical) (in watts)	[illegible]
Power consumption (max.) (in watts)	[illegible] (USB ports in use)
Max. Power consumption in stand-by mode (in watts)	0.5
Power consumption with power switch off (in watts)	0
Energy efficiency class	C
Energy consumption/1000h (in kWh)	11
Power supply	[illegible]
Power management	✓

DIMENSIONS & WEIGHT

Dimensions (incl. stand) (width x height x depth) (in mm)	499 x 351–411 x 233
Weight (incl. stand) (in kg)	5.5
Dimensions (without stand) (width x height x depth) (in mm)	499 x 321 x 54
Weight (without stand) (in kg)	3.4
Dimension drawing (PDF)	Dimension drawing (PDF)
Rotatability of the stand (in °)	344
Tiltability forwards/backwards (in °)	5 / 35
Pivot between portrait / landscape	clockwise and anti-clockwise
Height adjustment range (in mm)	110
Hole spacing	100 x 100

Experience the EV2360 in AR now!

The 22.5" IPS monitor with a 16:10 aspect ratio and a resolution of 1920 x 1200 pixels boosts the viewing angle, contrast ratio and brightness and helps deliver superb ergonomics for [illegible]. The clear display with an aspect ratio of 16:10 and a resolution of 1920 x 1200 pixels boosts [illegible] visual elements and colours are displayed crisply and clearly. The EV2360's optional Auto EcoView function automatically adjusts the screen's brightness. This reduces energy consumption and lowers CO2 emissions from power generation. As an added bonus, having the right brightness levels helps prevent distracting glare. This way, both the user and the environment benefit. The EV2360 is targeted at companies, government agencies and home users who are looking for a high-quality monitor.

- 22.5" LCD monitor with a 16:10 aspect ratio and IPS technology for outstanding image quality
- Bezel-[illegible] amazingly compact and ultra-elegant design
- Flicker-free, [illegible] reproduction thanks to hybrid brightness control
- Auto EcoView and EcoView Optimizer deliver maximum power savings and superb ergonomics
- Optimised antireflection properties and flexible positioning
- USB 3.1 hub with one upstream and two downstream ports
- DisplayPort, HDMI and D-sub signal inputs
- Proven to be environmentally friendly and produced in a socially responsible way
- 5-year warranty for highest investment security

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 15.07.2024