Austria, Hungary, Romania & Bulgaria
EIZO Austria GmbH

Pfarrgasse 87
1230 Vienna
Tel.: (+43-1) 6152886-10
www.eizo.at, www.eizo.hu

Belgium & Luxembourg
EIZO Europe GmbH

Antwerpsesteenweg 22
2860 Sint-Katelijne-Waver (Mechelen)
Tel.: (+32-15) 645-511
www.eizo.be

Czechia & Slovakia
EIZO Europe GmbH

Meteor Centre Office Park "B"
Sokolovská 100/94
186 00 Praha 8
Tel.: (+420-222) 319-714
www.eizo.cz, www.eizomonitor.sk

Germany
EIZO Europe GmbH

Belgrader Str. 2
41069 Mönchengladbach
Tel.: (+49-2161) 8210-0
www.eizo.de

Italy
EIZO Europe GmbH

Via Torino, 3/5
20814 – Varedo (MB)
Tel.: (+39-0362) 169-5250
www.eizo.it

The Netherlands
EIZO Europe GmbH

Dr. Holtroplaan 34-36
5652 XR Eindhoven
Tel.: (+31-40) 7600-360
www.eizo.nl

Scandinavia & Russia
EIZO Nordic AB

Lövängsvägen 14
SE-194 05 Upplands Väsby
Tel.: (+46-8) 5941-0500
www.eizo.se

Switzerland
EIZO AG

Moosacherstrasse 6, Au
8820 Wädenswil
Tel.: (+41-44) 782-2440
www.eizo.ch

UK
EIZO Limited

1 Queens Square
Ascot Business Park
Lyndhurst Road
Ascot | Berkshire
SL5 9FE
Tel.: (+44-1344) 317-480
www.eizo.co.uk

EIZO, the EIZO logo and ColorEdge are registered trademarks of the EIZO Corporation in Japan and other countries. ColorNavigator and Quick Color Match are trademarks of the EIZO Corporation.

Adobe and Photoshop are trademarks or registered trademarks of Adobe Systems Incorporated in the US and/or other countries. The terms HDMI, HDMI High Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing, LLC in the US and other countries. All other product names are trademarks or registered trademarks of the respective companies.

Copyright © 2021 EIZO Europe GmbH. All rights, errors and modifications are subject to change.
Last updated: March 2021

CG247X	CG279X	CG319X
24.1"/61 cm (diameter 611 mm)	27"/68 cm (diameter 684 mm)	31.1"/79 cm (diameter 789 mm)
[illegible]	2560 × 2560 (aspect ratio 1:1)	4096 × 2160 (aspect ratio 17:9)
518.4 × 324 mm	596.7 × 335.6 mm	698 × 368.1 mm
0.270 × 0.270 mm	0.233 × 0.233 mm	0.170 × 0.170 mm
94 ppi	109 ppi	149 ppi
[illegible]	[illegible]	DisplayPort, HDMI: 1024, from a palette of [illegible] tones
[illegible] colours	[illegible] colours	
DisplayPort, HDMI: 1.07 billion from a palette of 2.78 trillion colours (16 bit) DVI: 16.77 million from a palette of 2.78 trillion colours (16 bit)	USB Type-C, DisplayPort, HDMI: 1.07 billion from a palette of 2.78 trillion colours (16 bit) DVI: 16.77 million from a palette of 2.78 trillion colours (16 bit)	DisplayPort, HDMI: 1.07 billion colours from a 24-bit palette
178°, 178°	178°, 178°	178°, 178°
400 cd/m²	350 cd/m²	350 cd/m²
≤ 120 cd/m²	≤ 120 cd/m²	≤ 120 cd/m²
1500:1	1300:1	1500:1
◆	◆	◆
10 ms (grey-grey)	13 ms (grey-grey)	9 ms (grey-grey)
Adobe RGB 99%, DCI-P3 98%	Adobe RGB 99%, DCI-P3 98%	Adobe RGB 99%, DCI-P3 98%
DVI-D, 24-pin (with HDCP), DisplayPort (with HDCP 1.3), HDMI (with HDCP, Deep Color)	USB Type-C (with HDCP), DisplayPort (with HDCP), HDMI (with HDCP, Deep Color), DVI-D, 24-pin (with HDCP)	2 × DisplayPort (with HDCP 1.3), 2 × HDMI (with HDCP 1.3 and 2.2, Deep Color)
DisplayPort, DVI: [illegible]	USB Type-C, DisplayPort: 60 / 30 / 24 MHz, DVI: 165 MHz, HDMI: [illegible] MHz	DisplayPort: [illegible] MHz, HDMI: [illegible] MHz
2 × Type B, USB 2.0	1 × Type C, USB 3.1 Gen 1 (DisplayPort Alt Mode, 15 W power supply), 1 × Type B, USB 3.1 Gen 1	1 × Type B, USB 3.1 Gen 1
3 × Type A, USB [illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]
AC 100–120 V / AC 200–240 V, 50/60 Hz	AC 100–240 V / AC 200–240 V, 50/60 Hz	AC 100–240 V, 50/60 Hz
40 W/21 W/[illegible] W (Eco Mode), [illegible]	60 W/22 W/[illegible] W	80 W/22 W/[illegible] W
F	G	G
28 kWh	38 kWh	55 kWh
◆	◆	◆
◆	◆	◆
◆/◆	◆/◆	◆/◆
◆	◆	◆
◆	◆	◆
Colour mode (Adobe RGB, [illegible] Rec.709, EBU, SMPTE [illegible])	Colour mode (Adobe RGB, DCI-P3, Rec.709, EBU, DCI, PQ_BT.2100, HLG_BT.2100, Adobe RGB, sRGB, calibration)	Colour mode (BT.2020, BT.709, DCI, PQ_DCI, PQ_BT.2100, HLG_BT.2100, Adobe RGB, sRGB, calibration)
HLG, PQ curve (optional)	HLG, PQ curve	HLG, PQ curve
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆	◆	◆
◆/◆	◆/◆	◆/◆
575 × 417 – 543 × 245 mm/8.9 kg	618 × 416 – 570 × 265 mm/10.3 kg	715 × 434 – 588 × 290 mm/12.4 kg
135 mm	[illegible]	154 mm
30° to the back, 0° to the front/344°/90°	35° to the back, 5° to the front/344°/90°	35° to the back, 5° to the front/344°/–
100 × 100 mm	[illegible] mm	100 × 100 mm
CE, CB, TÜV/GS, TÜV certified ergonomics (including ISO 9241-307), TÜV/Color Accuracy (Quick Stability), FograCert Softproofing System (class A), cULus, TÜV/S, EAC, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, CCC, RoHS, China RoHS, WEEE	CE, CB, TÜV/GS, TÜV certified ergonomics (including ISO 9241-307), TÜV/Color Accuracy (Quick Stability), FograCert Softproofing System (class A), cULus, TÜV/S, EAC, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, CCC, RoHS, China RoHS, WEEE	CE, CB, TÜV/GS, TÜV certified ergonomics (including ISO 9241-307), TÜV/Color Accuracy (Quick Stability), FograCert Softproofing System (class A), cULus, TÜV/S, EAC, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, CCC, RoHS, China RoHS, WEEE
Power cord, signal cable (USB/HDMI – USB/HDMI), USB upstream cable, Set-up Guide, calibration certificate, cleaning set, light protection hood	Power cord, signal cable (DisplayPort – DisplayPort, USB/HDMI), USB upstream cable, Set-up Guide, calibration certificate, light protection hood	Power cord, signal cable (DisplayPort – DisplayPort, DisplayPort – DisplayPort, HDMI – HDMI), USB upstream cable, Set-up Guide, calibration certificate, cleaning set, light protection hood
◆	◆	◆
◆	◆	◆
Five years	Five years	Five years

◆ Standard, ◆ optional