

# Sandberg Survivor Powerbank 9in1 144000

## Specifications

Battery capacity: 3.2V/144000 mAh/460.8 Wh  
Battery pack capacity: 12.8V/36000 mAh/460.8 Wh  
Battery type: LiFePO<sub>4</sub> battery cells  
1 x DC input: 12-24V/5A (120W max)  
1 x Solar charging input: Up to 100W (MPPT control)  
1 x Small Anderson (solar input): 12-24V/8A (MPPT 160W max)  
1 x USB-C1 PD input: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W max)  
1 x USB-C1 PD output: 5W/3A, 9W/3A, 12V/3A, 15W/3A, 20V/5A (100W max)  
1 x USB-C2 PD output: 5W/3A, 9W/2A, 12V/2.25A, PPS 4.4-11V/3A  
2 x USB-A QC 3.0 outputs: 5V/3A, 9V/2A, 12V/1.5A (18W max each)  
2 x Car Lighter Socket: 12V/15A (180W max)  
1 x Big Anderson output: 12V/30A (360W max)  
IPX4 water-resistant  
Working temperature: 0°C to +40°C  
Operating temperature: 0°C to +40°C



## Packaging info

1 Sandberg Survivor Powerbank 9in1 144000  
1 AC charger, input AC 100-240V output DC 20V/2A 40W, cable length 1m (EU+UK plug)  
1 USB-C to USB-C charging cable, 75 cm  
1 Carry case  
1 Quick guide  
1 GPSR Safety guide

Quick guide: <https://sandberg.world/mv/manual/421-37>

## Dimensions

|             | Product  | Package  |
|-------------|----------|----------|
| Height (cm) | 8.10     | 24.00    |
| Width (cm)  | 22.00    | 22.00    |
| Depth (cm)  | 38.00    | 8.10     |
| Weight (g)  | 4,500.00 | 5,530.00 |



Product:  
[www.sandberg.world/product/survivor-powerbank-9in1-144000](https://www.sandberg.world/product/survivor-powerbank-9in1-144000)

Dealer: