

Sandberg Travel Charger PD140W Display

⚙ Specifications

World adapter plugs included: EU, UK, Australia (US plug built in)
Input: AC 100-240V 50/60Hz 2A Max
Output:
USB-C1: 5W/3A, 9W/3A, 12V/3A, 15W/3A, 20V/5A, 28W/5A (140W Max)
USB-C2: 5W/3A, 9W/3A, 12V/3A, 15W/3A, 20V/5A, 28W/5A (140W Max)
USB-A: 5V/3A, 9V/2A, 12V/1.5A (18W Max)
USB-C1+USB-C2: 100W+35W
USB-C1/C2+USB-A: 100W+18W
USB-C1+USB-C2+USB-A: 65W+45W+18W
Total output: 140W Max
V0 fire-proof PC housing
GaN charger
Digital display showing charging power, temperature, usage time and power distribution



📦 Verpakkingsinformatie

1 Sandberg Travel Charger PD140W Display
1 EU plug
1 UK plug
1 AUS plug
1 Carry pouch
1 GPSR Safety guide

Snelle gids: <https://sandberg.world/mt/manual/441-72>

↔ Afmetingen

	Product	Verpakking
Hoogte (cm)	6,90	15,00
Breedte (cm)	6,90	12,00
Diepte (cm)	3,30	5,00
Gewicht (g)	265,00	340,00



Product:
www.sandberg.world/product/travel-charger-pd140w-display

Dealer: