

Technical Data

GENERATION & STANDARDS

Certification	CCC, CE, FCC, RoHS, TÜV/Ergonomics (including ISO 9241-301/302), TÜV/Certified Generation 2 EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, BSM, FCC-B, CAN ICES-3 (B), TÜV SPS, VCCI-B, GS, LONDOY STAR, RoHS, WEEE, China RoHS, CCC, BSM, EAC
Case color	Black
Area of application	Office
SOFTWARE & ACCESSORIES	Free
Accompanying software and other accessories	Screen Inquiry Large and medium-sized companies, Private user & small business, Finance
Control/adjustment elements	Touchscreen, On-screen menu, Quick
S.A.N.	890504700000
Accessories	Power supply, H-DCP-R-K, PC

WARRANTY

Screen (panel/tech spec)	23.6" for unit and LCD module up to 30000 operating hours, whichever comes first.
Screen size (in mm)	592
Included warranty	Zero pixel defects guarantee, no fully illuminated sub-pixels (sub-pixel ISO 9241-307) for six months from date of purchase.

Viewable image size (width x height) (in mm)	498.2 x 297.2
--	---------------

Resolution	1920 x 1200
------------	-------------

Pixel pitch	0.254 x 0.254
-------------	---------------

Pixel pitch	0.254 x 0.254
-------------	---------------

Super wide	1920 x 1200
------------	-------------

Auto	1920 x 1200
------	-------------

Max. viewing angle horizontal	178
-------------------------------	-----

Max. viewing angle vertical	178
-----------------------------	-----

Number of colors or greyscale	16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DVI, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit)
-------------------------------	---

Color pattern/look-up table	10-bit color, 10-bit color, 10-bit color
-----------------------------	--

Max. color space (typical)	sRGB
----------------------------	------

Max. dynamic contrast (typical)	1000:1
---------------------------------	--------

Flicker-free image reproduction thanks to hybrid brightness control	LED
---	-----

Backlight	LED
-----------	-----

Auto EcoView and EcoView Optimizer deliver maximum power savings and superb ergonomics	Auto EcoView and EcoView Optimizer
--	------------------------------------

Signal inputs	D-Sub, DisplayPort (HDCP 1.3), HDMI (HDCP 1.4)
---------------	--

USB specification	USB 3.0 (USB 3)
-------------------	-----------------

USB upstream ports	1 x type B
--------------------	------------

USB downstream ports	2 x type A
----------------------	------------

Graphic signal	RGB Analog, DisplayPort, HDMI (RGB, YUV)
----------------	--

Sync formats	Separate
--------------	----------

Find your EIZO contact	3.5 mm stereo jack, DisplayPort, HDMI
------------------------	---------------------------------------

Audio/headphone input	3.5 mm stereo jack
-----------------------	--------------------

Phone	3.5 mm stereo jack
-------	--------------------

www.eizo.eu	
-------------	--

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgardstr. 2, 40699 Mönchengladbach, Germany. All rights, errors and modifications reserved. Last update: 15.07.2024	
--	--

FEATURES & OPERATION

Preset color/greyscale modes	2x manual memory locations, sRGB, Paper, Movie, DICOM
DICOM tone curve	✓
Auto EcoView	✓
EcoView Index	✓
EcoView Optimizer	✓
Overdrive	✓
No flickering	✓
HDCP Decoder	✓
Automatic signal input recognition	✓
Built-in speakers	✓
On-screen menu languages	de, en, fr, es, it, zh
Adjustment options	Color Mode, Brightness, Contrast, Color temperature, Gamma, Color saturation, Resolution, Scaling, OSD language, Signal Input, All EcoView functions, Volume
Button Guide	✓
Integrated power unit	✓

ELECTRICAL DATA

Power consumption	Display Port: 21.755 W (20.61 Hz), HDMI: 15.755 W (14.61 Hz), D-Sub: 15.755 W (14.61 Hz)
-------------------	--

Power consumption in stand-by mode (in watts)	0.5
---	-----

Power consumption with power switch off (in watts)	0
--	---

Optimised antireflection properties and flexible positioning	Energy efficiency class C
--	---------------------------

Energy consumption/1000h (in kWh)	11
-----------------------------------	----

USB 3.1 hub with one upstream and two downstream ports	Power management
--	------------------

DisplayPort, HDMI and D-sub signal inputs	✓
---	---

Proven to be environmentally friendly and produced in a socially responsible way	Dimensions (incl. stand) (width x height x depth) (in mm)
--	---

Weight (incl. stand) (in kg)	5.5
------------------------------	-----

5-year warranty for highest investment security	Dimensions (without stand) (width x height x depth) (in mm)
---	---

Weight (without stand) (in kg)	3.4
--------------------------------	-----

Dimension drawing (PDF)	Dimension drawing (PDF)
-------------------------	-------------------------

Rotatability of the stand (in °)	344
----------------------------------	-----

Tilting forwards/backwards (in °)	5 / 35
-----------------------------------	--------

Pivot between portrait / landscape	clockwise and anti-clockwise
------------------------------------	------------------------------

Height adjustment range (in mm)	140
---------------------------------	-----

Idle spacing	100 x 100
--------------	-----------

Experience the EV2360 in AR now!

