# Technical Data

## DIMENSIONS & WEIGHT

| | |
|---|---|
| Dimensions (incl. stand) (width x height x depth) (in mm) | 610/664.88-814.5 x 210 x 362.75-447 |
| Weight (incl. stand) (in kg) | 8.85 kg |
| Dimensions (without stand) (width x height x depth) (in mm) | 610 x 364.5-414.5 x 54.7 (Center) |
| Weight (without stand) (in kg) | 5.6 kg (Center) |
| Dimensions drawing (PDF) | Dimension drawing-EIZO companies, Private user 8 |
| Rotability of the stand (in °) | 344 |
| Specific system requirements | Systems including macOS and Windows |
| Tiltability forwards/backwards (in °) | 35 / 5 |
| Pivot between portrait / landscape | Available / Available |
| Height adjustment range (in mm) | 149 |

## SCREEN

| | |
|---|---|
| Pixel pitching | 0.233 x 0.233 |
| Screen size (in inches) | 27 |
| Screen size in cm | 68.5 |
| Format | 16:9 |
| Viewable image size (width x height) (in mm) | 597.9 x 336.3 |
| Ideal and recommended resolution | 2560 x 1440 |

## CERTIFICATION & STANDARDS

| | |
|---|---|
| Certification | CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, VCCI, FCC-B, CAN ICES-3 (B), TÜV/S, ENERGY STAR, RoHS, WEEE, China RoHS, UKCA, EAC |

## SOFTWARE & ACCESSORIES

| | |
|---|---|
| Software | EcoUtilities |
| Supported resolutions | 2560 x 1440, 1920 x 1200, 1920 x 1080 (Full HD), 1680 x 1050, 1600 x 1200, 1440 x 900, 1280 x 1024, 1280 x 960, 1280 x 720, 1024 x 768, 720 x 480, 640 x 480 |
| Other box contents | USB cable (Type A - Type B), signal cable (DisplayPort), USB cable (Type A - Type B), signal cable (HDMI), power cable, quick start guide |
| Panel technology | IPS |
| Accessories | PM200K, CP200, HD200PMK, BC3K83 |

## WARRANTY

| | |
|---|---|
| Warranty period | 5 years |
| Warranty period for sub-pixels or greyscale | Sub-pixel color and DVC (Dead Pixel Guarantee) according to ISO 9241-307 (class 1) (DisplayPort & HDMI interfaces) (HDMI, 8 Bit) |
| Warranty period for backlight | 5 years, 50,000 hours (25,000 hours for sub-pixel defects according to ISO 9241-307) for six months from date of purchase |

## CONNECTIVITY

| | |
|---|---|
| Signal inputs | 2x DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), DVI-D (HDCP 1.4) |
| USB specification | USB 5Gbps (USB 3) |
| USB upstream ports | 1 x type B |
| USB downstream ports | 4x type A |
| Graphic signal | DisplayPort, HDMI (RGB, YUV), DVI Dual Link (TMDS) |
| Sync formats | Separate |
| Audio input | 3.5 mm stereo jack, DisplayPort, HDMI |
| Audio / headphone output | 3.5 mm stereo jack |

## FEATURES & OPERATION

| | |
|---|---|
| Preset color/greyscale modes | 2x manual memory locations, sRGB, Paper, Movie, DICOM |
| DICOM tone curve | ✓ |
| Auto EcoView | ✓ |
| EcoView Index | ✓ |
| EcoView Optimizer | ✓ |
| Overdrive | ✓ |
| No flickering | ✓ |
| HDCP Decoder | ✓ |
| Automatic signal input recognition | ✓ |
| Imagen por imagen | ✓ |
| Built-in speakers | ✓ |
| On-screen menu languages | de, en, fr, es, it, ja |
| Adjustment options | Color Mode, Brightness, Contrast, Color temperature / White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal Input, All EcoView functions, Volume |
| Button Guide | ✓ |
| Integrated power unit | ✓ |

## ELECTRICAL DATA

| | |
|---|---|
| Frequency | DisplayPort: 31-89 kHz / 59-61 Hz (69-71 Hz), HDMI: 31-89 kHz / 59-61 Hz (69-71 Hz) |
| Power consumption (typical) (in watts) | 35 |
| Maximum Power Consumption (in watts) | 67 (at maximum brightness with all signal inputs and USB ports in use) |
| Max. Power consumption in stand-by mode (in watts) | 0.5 |
| Power consumption with power switch off (in watts) | 0 |
| Energy efficiency class | E |
| Energy consumption/1000h (in kWh) | 18 |
| Power supply | AC 100-240V, 50/60Hz |
| Power management | ✓ |

→ Product Website → Experience in AR

# 27" Office Monitor

With a large screen 27-inch diagonal and a resolution of 2560 x 1440 pixels, the EV2760 offers all the space that's needed for efficient use in the office. No matter if it's text, graphics or videos, users enjoy crystal clear, incredibly detailed image reproduction on its large screen. Anti-reflection coating, flicker-free brightness control and a flexible stand facilitate ergonomic work. Its smart, three-sided virtually frameless design means that you focus on what's most important while maintaining a clear overview of your work. Thanks to its EcoView functions, it boasts a low power consumption if, for example, you need a lower brightness level and a glare-free view. The EV2760 offers a wide range of connection possibilities with Display Port, HDMI and DVI-D signal inputs – not to mention four USB downstream ports.

- 27-inch IPS LCD monitor with a resolution of 2560 x 1440 pixels for excellent image quality
- Bezel-only design for a compact and ultra-elegant design
- Excellent image reproduction thanks to hybrid bright-ness control
- Optimised anti-reflection properties and flexible posi-tioning
- USB 3.1 hub with one upstream and four downstream ports
- 2 x DisplayPort, HDMI, DVI-D and D-Sub signal inputs
- Proven to be environmentally friendly and produced in a socially responsible way
- 5-year warranty for highest investment security

**Experience the EV2760 in AR now!**

Find your EIZO contact
EIZO Europe GmbH
Belgrader Straße 2
41069 Mönchengladbach
www.eizo.eu

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 21.07.2024