EIZO ACADEMY

Because you never stop getting better

In the EIZO Academy you will find an extensive range of video tutorials, technical articles, seminars and workshops. Accompany us to the Lofoten islands or through Namibia – in our two Colourclass video series, our experts give you extensive tips on monitor calibration, color management and soft proofing. They also provide in-depth knowledge on numerous photographic topics. You will also find specialist articles with detailed monitor knowledge. You can find everything about the EIZO Academy and the current dates of our seminars, workshops and webinars at: **www.eizo.academy**

So

As vr … comr … unad …

… of application are, they all have one thing in …

Abs… from …

Lossle…

Perio… the sa… monit… the … Calibration … graph…

… osely checked and, if necessary, corrected. This elaborate …

		…00R	CS2400S	CS2731	CS2740
Display	Type	[illegible]	[illegible]	[illegible]	IPS
	Screen size	24.1"/61.1 cm	24.1"/61.1 cm	27"/68.5 cm	26.9"/68.4 cm
	Native resolution	[illegible]	[illegible]	[illegible]	3,840 × 2,160 (UHD)
Video signal	Inputs	[illegible] Deep Color)	[illegible] Deep Color)	[illegible] Color), DVI-D (with HDCP)	[illegible] HDMI (with HDCP, Deep Color)
	Outputs	–	–	–	–
	Scanning frequency	[illegible] DVI: 26 – 76 kHz, 23 – 61 Hz	DisplayPort, DVI: 26 – 76 kHz, 23 – 61 Hz	USB Type C, DisplayPort, DVI: 26 – 89 kHz, 23 – 61 Hz	USB Type C, DisplayPort: 25 – 137 kHz, 23 – 61 Hz [illegible]
USB	Upstream	1 × Type C, USB 5 Gbps (DisplayPort [illegible]), 1 × Type B, USB 5Gbps	1 × Type C, USB 5 Gbps (DisplayPort [illegible]), 1 × Type B, USB 5Gbps	1 × Type C, USB 5 Gbps (DisplayPort [illegible]), 1 × Type B, USB 5 Gbps	1 × Type C, USB 5 Gbps (DisplayPort [illegible]), 1 × Type B, USB 5Gbps
	Downstream	[illegible] 2 × USB 2.0)	[illegible] 2 × USB 2.0)	[illegible] 2 × USB 2.0)	[illegible] 2 × USB 2.0)
LAN connection		[illegible]	[illegible]	[illegible]	[illegible]
Audio	Inputs	[illegible]	[illegible]	[illegible]	[illegible]
	Outputs	[illegible]	[illegible]	[illegible]	[illegible]
Power supply	Power input	100 – 240 V AC, 50/60 Hz	100 – 240 V AC, 50/60 Hz	100 – 240 V AC, 50/60 Hz	100 – 240 V AC, 50/60 Hz
	Max. power consumption / typical power consumption / power save mode / stand-by mode	134 W / 15 W / ≤ 0.3 W / ≤ 0.3 W	149 W / 18 W / ≤ 0.3 W / ≤ 0.3 W	159 W / 34 W / ≤ 1 W / ≤ 1 W	168 W / 36 W / ≤ 1 W / ≤ 1 W
	Energy efficiency class	F	E	G	G
	Energy consumption / 1000 h	19 kWh	16 kWh	35 kWh	38 kWh
Calibration	Integrated calibration sensor and self-calibration	–	–	–	–
Shading Hood		◇	◇	◇	◇
Features and functions	Hardware calibration / 3D look-up table	◆/–	◆/–	◆/–	◆/–
	Brightness stabilisation	–	–	–	–
	Digital Uniformity Equalizer	◆	◆	◆	◆
	Preset modes	Colour modes (sRGB, Calibration, Custom)	Colour modes (AdobeRGB, sRGB, Calibration, Custom)	Colour modes (AdobeRGB, sRGB, Calibration, User)	Colour modes (AdobeRGB, sRGB, Calibration, User)
	HDR gamma	–	–	–	HLG, PQ curve (optional)
	ColorNavigator Network support	◆	◆	◆	◆
	CMYRGB colour control	◆	◆	◆	◆
	CMYK validation	–	–	–	–
	Colour temperature setting	◆	◆	◆	◆
	LUT system with post-LUT and factory-calibrated pre-LUT	◆	◆	◆	◆
	Gamut clipping	◆	◆	◆	◆
	DUE priority	◆	◆	◆	◆
	DCI 4K trimming	–	–	–	–
	Safe area marker / Pixel inspection	–/–	–/–	–/–	–/–
	Support for progressive and interlaced signal formats	◆	◆	◆	◆
	Signal range extension (HDMI)	◆	◆	◆	◆
	Support for YUV signal (DisplayPort and HDMI input)	◆	◆	◆	◆
	3D LUT film emulation (support for LogView LUT)	–	–	–	–
	KVM switch	◆	◆	◆	◆
	User-specific button assignment	◆	◆	◆	–
	Button guide (button layout overview)	◆	◆	◆	◆
	Operation in portrait and landscape format	◆	◆	◆	◆
Dimensions and weight	Dimensions (W × H × D, landscape format) / Net weight	554.4 × 396 – 551 × 245 mm / 8.1 kg	554.4 × 396 – 551 × 245 mm / 8.2 kg	638 × 404 – 559 × 265 mm / 10.1 kg	638 × 404 – 559 × 265 mm / 10.3 kg
	Height adjustment range	155 mm	155 mm	155 mm	155 mm
	Tilt/Swivel/Rotation angles	35° to the back, 5° to the front / 344° / 90°	35° to the back, 5° to the front / 344° / 90°	35° to the back, 5° to the front / 344° / 90°	35° to the back, 5° to the front / 344° / 90°
	VESA	100 × 100 mm	100 × 100 mm	100 × 100 mm	100 × 100 mm
Certifications and standards	Current information is available from EIZO or the sales and distribution partners in your country	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE
Supplied accessories		Power cord, signal cable (HDMI – HDMI, USB-C – USB-C), USB-cable, Set-up Guide, Calibration certificate	Power cord, signal cable (HDMI – HDMI, USB-C – USB-C), USB-cable, Set-up Guide, Calibration certificate	Power cord, signal cable (HDMI – HDMI, USB-C – USB-C), USB-cable, Set-up Guide	Power cord, signal cable (DisplayPort – DisplayPort, USB-C – USB-C), USB-cable, Set-up Guide
Quality and warranty	[illegible]	◆	◆	◆	[illegible]
	[illegible]	–	–	–	[illegible]
	Warranty with on-site exchange service[2]	Five years	Five years	Five years	[illegible]

[1] Free from bright sub-pixels (partial image elements ISO 9241-307) six months following original purchase date.



CG2400S | CG2400SV	CG2700S	CG2700X	CG3100X
IPS	IPS	IPS	IPS
24.1"/61.1 cm	27"/68.5 cm	26.9"/68.4 cm	30.5"/77.5 cm
[illegible]	2560 × 1440 (Aspect ratio 16:9)	[illegible]	[illegible]
518.4 × 324 mm	596.7 × 335.7 mm	596.2 × 335.3 mm	685.7 x 361.6 mm
0.270 × 0.270 mm	0.233 × 0.233 mm	0.155 × 0.155 mm	[illegible]
94 ppi	109 ppi	164 ppi	152 ppi
[illegible]	[illegible]	[illegible]	[illegible]
178°, 178°	178°, 178°	178°, 178°	178°, 178°
400 cd/m²	400 cd/m²	500 cd/m²	500 cd/m²
1800:1	1500:1	1450:1	1800:1
◆	◆	[illegible]	◆
11 ms (grey-grey)	19 ms (grey-grey)	13 ms (grey-grey)	15 ms (grey-grey)
AdobeRGB (>99 %), DCI-P3 (>98 %)	[illegible] 98 %	AdobeRGB 9[illegible]	AdobeRGB 97%, DCI-P3 9[illegible]
USB Type C (with DisplayPort Alt Mode and HDCP)[4], BNC (3G Level A/HD-SDI)[5], DisplayPort (with HDCP), HDMI (with HDCP, Deep Color)	USB Type C (with DisplayPort Alt Mode, HDCP), DisplayPort (with HDCP), HDMI (with HDCP, Deep Color)	USB Type C (with DisplayPort Alt Mode, HDCP), DisplayPort (with HDCP), HDMI (with HDCP, Deep Color)	USB Type C (with DisplayPort Alt Mode, HDCP), DisplayPort (with HDCP), HDMI with FRL, HDCP, Deep Color
–[4], BNC (3G [illegible])	[illegible]	[illegible]	[illegible]
USB Type C[4], DisplayPort: 26 – 76 kHz, 23 – 61 Hz HDMI: 15 – 76 kHz, 24 – 61 Hz	USB Type C, DisplayPort: 26 – 89 kHz, 23 – 61 Hz HDMI: 15 – 89 kHz, 23 – 61 Hz	USB Type C, DisplayPort: 25 – 137 kHz, 23 – 61 Hz HDMI: 15 – 135 kHz, 23 – 61 Hz	USB Type C, DisplayPort: 25 – 137 kHz, 23 – 61 Hz HDMI: 15 – 135 kHz, 23 – 61 Hz
1 × Type C, USB 5Gbps (DisplayPort Alt Mode, 70 W power delivery), 1 × Type B, USB 5 Gbps[4], 2 × Type B, USB 5 Gbps[5]	1 × Type C, USB 5Gbps (DisplayPort Alt Mode, 92 W power delivery), 1 × Type B, USB 5Gbps	1 × Type C, USB 5Gbps (DisplayPort Alt Mode, 94 W power delivery), 1 × Type B, USB 5 Gbps	1 × Type C, USB 5Gbps (DisplayPort Alt Mode, 94 W power delivery), 1 × Type B, USB 5Gbps
4 × Type A (2 × USB 5Gbps, 2 × USB 2.0)	4 × Type A (2 × USB 5Gbps, 2 × USB 2.0)	4 × Type A (2 × USB 5Gbps, 2 × USB 2.0)	4 × Type A (2 × USB 5Gbps, 2 × USB 2.0)
–	RJ-45 (1000BASE-T)	RJ-45 (1000BASE-T)	RJ-45 (1000BASE-T)
–[4], DisplayPort, HDMI, SDI[5]	–	–	–
–[4], 3,5 mm Stereo-Klinke-Buchse[5]	–	[illegible]	[illegible]
100 – 240 V AC, 50/60 Hz	100 – 240 V AC, 50/60 Hz	100 – 240 V AC, 50/60 Hz	100 – 240 V AC, 50/60 Hz
150 W / 17 W / ≤ 0.5 W / ≤ 0.3 W[4], 64 W / 18 W / ≤ 0.5 W[5]	187 W / 17 W / ≤ 0.5 W / ≤ 0.3 W	225 W / 34 W / ≤ 0.5 W / ≤ 0.5 W	270 W / 86 W / ≤ 0.5 W / ≤ 0.5 W
E[4]	E	G	G
15 kWh[4]	18 kWh	35 kWh	51.9 kWh
◆	◆	◆	◆
◆	◆	◆	◆
◆/◆	◆/◆	◆/◆	◆/◆
◆	◆	◆	◆
◆	◆	◆	◆
Colour modes (AdobeRGB[4], sRGB, BT.2020, BT.709, DCI-P3, PQ_DCI-P3, HLG_BT.2100, PQ_BT.2100[5], Calibration, SYNC_SIGNAL, User)	Colour modes (AdobeRGB, sRGB, BT.2020, BT.709, DCI-P3, PQ_DCI-P3, HLG_BT.2100, Calibration, SYNC_SIGNAL, User)	Colour modes (AdobeRGB, sRGB, BT.2020, BT.709, DCI-P3, PQ_DCI-P3, HLG_BT.2100, Calibration, SYNC_SIGNAL, User)	Colour modes (AdobeRGB, sRGB, BT.2020, BT.709, DCI-P3, PQ_DCI-P3, HLG_BT.2100, Calibration, SYNC_SIGNAL, User)
HLG, PQ curve	HLG, PQ curve	HLG, PQ curve	HLG, PQ curve
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
–	–	◆	–
◆/◆	◆/◆	◆/◆	◆/◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	◆
◆	◆	◆	–
554.4 × 408.1 – 563.1 × 245 mm / 8.5 kg	638 × 416 – 571 × 245 mm / 9.4 kg	638 × 416 – 571 × 245 mm / 9.8 kg	721 × 428.1 – 583.1 × 290 mm / 12.5 kg
155 mm	155 mm	155 mm	155 mm
35° to the back, 5° to the front / 344° / 90°	35° to the back, 5° to the front / 344° / 90°	35° to the back, 5° to the front / 344° / 90°	35° to the back, 5° to the front / 344° / –
100 × 100 mm	100 × 100 mm	100 × 100 mm	100 × 100 mm
CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), FograCert Softproofing System (class A)[4], cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), TÜV/Color Accuracy (Quick Stability), FograCert Softproofing System (class A), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), TÜV/Color Accuracy (Quick Stability), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE	CE, CB, UKCA, TÜV/GS, TÜV Certified ergonomics (including ISO 9241-307), TÜV/Color Accuracy (Quick Stability), FograCert Softproofing System (class A), cTÜVus, TÜV/S, PSE, FCC-B, CAN ICES-3(B), RCM, VCCI-B, RoHS, WEEE
Power cord, signal cable (HDMI – HDMI, USB-C – USB-C[4], DisplayPort – DisplayPort[5]), USB cable, Set-up Guide, Calibration certificate, Shading Hood	Power cord, signal cable (HDMI – HDMI, USB-C – USB-C), USB cable, Set-up Guide, Calibration certificate, Shading Hood	Power cord, signal cable (HDMI – HDMI, USB-C – USB-C), USB cable, Set-up Guide, Calibration certificate, Shading Hood	Power cord, signal cable (HDMI – HDMI, USB-C – USB-C), USB cable, Set-up Guide, Calibration certificate, Shading Hood
◆	◆	◆	◆
◆	◆	◆	◆
Five years	Five years	Five years	Five years

[3] Up to a maximum of 30,000 hours of monitor usage time.
[4] CG2400S only
[5] CG2400SV only

◆ standard, ◇ optional

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies.

Copyright © 2025 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and changes reserved.

Last updated: August 2025

Working with the Best