

Sandberg Charger PD65W Display + Cable

Specifications

Input: AC 100-240V 50/60Hz 1.5A Max
Output:
USB-C (cable): 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-C: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65W Max)
USB-A: 5V/3A, 9V/3A, 10V/2.25A, 12V/2.5A, 20V/1.5A (30W Max)
USB-C (cable)+USB-C: 45W+20W (65W Max)
USB-C (cable)+USB-A: 45W+18W (63W Max)
USB-C+USB-A: 5V/3A (15W Max)
USB-C (cable)+(USB-C+USB-A): 45W+15W (60W Max)
Cable length: 60 cm
Total output: 65W Max
V0 fire-proof PC housing
GaN charger
Digital display showing charging power, temperature, usage time and power distribution



Packaging info

1 Sandberg Charger PD65W Display + Cable
1 GPSR Safety guide

Quick guide: <https://sandberg.world/mw/manual/441-74>

Dimensions

	Product	Package
Height (cm)	6.70	12.30
Width (cm)	5.50	10.00
Depth (cm)	5.00	5.50
Weight (g)	165.00	230.00



Product:
www.sandberg.world/product/charger-pd65w-display-cable

Dealer: