

Sandberg Solar Powerbank CampLED 20000

Specifications

Capacity: 20000mAh@3.7V / 74Wh
IP 65 water- shock and dustproof
USB-C1 Input: 5V/3A, 9V/2A, 12V/1.5A (PD18W max)
USB-C2 Input: 5V/3A, 9V/2A, 12V/1.5A (PD18W max)
USB-C1 Output: 5V/3A, 9V/2.2A, 12V/1.67A (PD20W max)
USB-C2 Output: 5V/3A, 9V/2.2A, 12V/1.67A (PD20W max)
USB-A Output: 5V/3A, 9V/2A, 12V/1.5A, SCP 10W/2.25A (22.5W max)
USB-C + USB-A Outputs (total): 5V/3A (15W max)
Solar panel: 250mA/5V (1.25W max)
Support Power-Through: Yes
Always-ON mode
Power stays on at above 60 mA power consumption
Auto power off after 2 hours below 60 mA power consumption
LED camp light: 200 lumens
Color temperature: 6000-6500K
Charging time by sun 0-25%: 15 hours (at ideal sunlight)
Charging time by USB-C 0-100%: 5 hours (USB-C 18Watt)
Charge temperature: 0-45°
Discharge temperature: -10-60°
PPS version: 5-11.0V 2.00A



Packaging info

1 Sandberg Solar Powerbank CampLED 20000
1 Quick guide
1 GPSR Safety guide
1 USB-C to USB-C charge cable 30cm
1 Lanyard
1 Lanyard ring

Quick guide: <https://sandberg.world/mv/manual/421-24>

Dimensions

	Product	Package
Height (cm)	14.80	17.40
Width (cm)	7.60	9.90
Depth (cm)	3.40	4.80
Weight (g)	450.00	550.00



Product:

www.sandberg.world/product/solar-powerbank-camp-led-20000

 Sandberg®

Dealer: