

Technical Data

DIMENSIONS & WEIGHT

Dimensions (incl. stand) (width x height x depth) (in mm)	610 (634) x 513 x 210 (62 (65) mm)
Weight (incl. stand) (in kg)	8.6 (8.7)
Dimensions (without stand) (width x height x depth) (in mm)	511 x 49.4 x 53.7 (51.6)
Weight (without stand) (in kg)	5.6 (5.6)
Mounting plate (PDF)	Click here to download the mounting plate PDF file.
Rotatability of the stand (in °)	±45
Speed of rotation (in degrees per minute)	10
Tiltability forwards/backwards (in °)	±5 (±5.5)
Angle between portrait / landscape	90°

Height adjustment range (in mm)	89
---------------------------------	----

Panel spacing	100 x 100
---------------	-----------

Screen size (in inches)	27
-------------------------	----

CERTIFICATION & STANDARDS

Certification	CE, UKCA, CB, TÜV GS, TÜV Ergonomics (including 9241-307), TCO Certified Generation 9, BFEAT 2018 (US), TÜV Blue Low Light Content, TÜV Flicker Free, BSM, e-tilt, PCC-B, CAN ICES-3 (B), TÜV SÜD, FCC, RoHS, REACH, RoHS, WEEE, China RoHS, CB, CCC, etc.
Viewable image area (width x height) (in mm)	598 x 336
Pixel pitch (in mm)	0.233 x 0.233

FEATURES & ACCESSORIES

With an impressive 27-inch diagonal and a resolution of 2560 x 1440 pixels, the EV2760 offers all the space that's needed for efficient use in the office. No matter if it's text, graphics or videos, users enjoy crystal clear, incredibly detailed image reproduction on its large screen. Anti-reflection coating, flicker-free brightness control and a flexible stand facilitate ergonomic work. Its smart, three-sided virtually frameless design means that you focus on what's most important while maintaining a clear overview of your work. Thanks to its EcoView functions, it boasts a low power consumption if, for example, you need a lower brightness and a glare-free view. The EV2760 offers a wide range of connection possibilities with DisplayPort, HDMI and DVI-D signal inputs – not to mention four USB downstream ports.	
--	--

WORKING CONDITIONS

Working conditions or grayscale	5 (10-bit color) / 10-bit color (optional) / 10-bit color (optional) / 10-bit color (optional) / 10-bit color (optional)
---------------------------------	--

27-INCH IPS LCD MONITOR WITH A RESOLUTION OF 2560 x 1440 PIXELS FOR EXCELLENT IMAGE QUALITY

Max. color space (typical)	95% (DCI-P3)
----------------------------	--------------

BEZEL-LESS DESIGN FOR A COMPACT AND ULTRA-ELEGANT DESIGN

Bezel width (mm)	2.0 (2.0)
------------------	-----------

EXCELLENT IMAGE REPRODUCTION THANKS TO HYBRID BRIGHTNESS CONTROL

Resolution	2560 x 1440
------------	-------------

EXPERIENCE THE EV2760 IN AR NOW!

Resolution	2560 x 1440
------------	-------------

2 x DISPLAYPORT, HDMI, DVI-D AND D-SUB SIGNAL INPUTS

Signal inputs	2x DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), DVI-D (HDCP 1.4)
---------------	--

USB SPECIFICATION

USB specification	USB 5 Gbps (USB 3)
-------------------	--------------------

USB UPSTREAM PORTS

USB upstream ports	1x type B
--------------------	-----------

USB DOWNSTREAM PORTS

USB downstream ports	4x type A
----------------------	-----------

GRAPHIC SIGNAL

Graphic signal	DisplayPort, HDMI (RGB, YUV), DVI Dual Link (TMDS)
----------------	--

SYNC FORMATS

Sync formats	Separate
--------------	----------

AUDIO

Audio	3.5 mm stereo jack, DisplayPort, HDMI
-------	---------------------------------------

AUDIO / HEADPHONE OUTPUT

Audio / headphone output	3.5 mm stereo jack
--------------------------	--------------------

FEATURES & OPERATION

Reset color/grayscale modes	2x manual memory locations, sRGB, Paper, Movie, DICOM
OSD top curve	✓
Auto EcoView	✓
EcoView Index	✓
EcoView Optimizer	✓
OS Drive	✓
Mouse/Keyboard	✓
Hotkey Decoder	✓
Automatic signal input recognition	✓

Image per image	✓
-----------------	---

Built-in speakers	✓
-------------------	---

ON-SCREEN MENU LANGUAGES

On-screen menu languages	de, en, fr, es, it, zh
--------------------------	------------------------

ADJUSTMENT OPTIONS

Adjustment options	Color Mode, Brightness, Contrast, Color temperature / White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal Input, All EcoView functions, Volume
--------------------	--

Button Guide	✓
--------------	---

Integrated power unit	✓
-----------------------	---

ELECTRICAL DATA

Frequency	DisplayPort 31.89 kHz / 59.51 Hz (69.71 Hz) HDMI 31.89 kHz / 59.51 Hz (69.71 Hz)
-----------	--

Power consumption (typical) (in watts)	20
--	----

Maximum Power Consumption (in watts)	67 (at maximum brightness with all signal inputs and USB ports in use)
--------------------------------------	--

Max. Power consumption in stand-by mode (in watts)	0.5
--	-----

Optimised anti-reflection properties and flexible positioning

Energy efficiency class	E
-------------------------	---

USB 3.1 hub with one upstream and four downstream ports

Energy consumption/1000h (in kWh)	18
-----------------------------------	----

Power supply

Power supply	AC 100-240V, 50/60 Hz
--------------	-----------------------

2 x DisplayPort, HDMI, DVI-D and D-Sub signal inputs

Power management	✓
------------------	---

Proven to be environmentally friendly and produced in a socially responsible way

5-year warranty for highest investment security	✓
---	---