# FlexScan monitors at a glance

Premium | Professional | Basic

Autumn 2026

FlexScan

| | EV4340X | EV3... | ...795 | EV2495 | EV2490 | EV2740S | EV2720S | EV2485 | EV2480 | EV2410R | EV2400R | EV2360 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Screen size | 42.5" Aspect ratio 16:9 | 37.5" Aspect ratio 24:10 Curved Ultrawide | 37.5" Aspect ratio 24:10 Curved Ultrawide | 34.1" Aspect ratio 21:9 Curved Ultrawide | 34.1" Aspect ratio 21:9 Curved Ultrawide | 31.5" Aspect ratio 16:9 | 27" Aspect ratio 16:9 | 27" Aspect ratio 16:9 | 24.1" Aspect ratio 16:10 | 23.8" Aspect ratio 16:9 | 27" Aspect ratio 16:9 | 27" Aspect ratio 16:9 | 24.1" Aspect ratio 16:10 | 23.8" Aspect ratio 16:9 | 24.1" Aspect ratio 16:10 | 23.8" Aspect ratio 16:9 | 22.5" Aspect ratio 16:10 |
| Resolution | 3,840×2,160 (4K UHD) | 3,840×1,600 | 3,840×1,600 | 3,440×1,440 | 3,440×1,440 | 3,840×2,160 (4K UHD) | 3,840×2,160 (4K UHD) | 2,560×1,440 | 1,920×1,200 | 1,920×1,080 | 3,840×2,160 (4K UHD) | 2,560×1,440 | 1,920×1,200 | 1,920×1,080 | 1,920×1,200 | 1,920×1,080 | 1,920×1,200 |
| Max. Brightness | 350 cd/m² | 300 cd/m² | 300 cd/m² | 300 cd/m² | 350 cd/m² | 350 cd/m² | 350 cd/m² | 350 cd/m² | 350 cd/m² | 250 cd/m² | 350 cd/m² | 350 cd/m² | 350 cd/m² | 250 cd/m² | 350 cd/m² | 350 cd/m² | 250 cd/m² |
| Signal inputs | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>2× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× USB-C<br>1× DisplayPort<br>1× HDMI | 1× DisplayPort<br>1× HDMI<br>1× DVI-D<br>1× D-Sub | 1× DisplayPort<br>1× HDMI | 1× DisplayPort<br>1× HDMI<br>1× D-Sub |
| USB ports | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>2× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>2× USB-B<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>2× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>1× USB-B<br>Downstream:<br>1× USB-C<br>3× USB-A | Upstream:<br>1× USB-C<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-C<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-C<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-C<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-B<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-B<br>Downstream:<br>4× USB-A | Upstream:<br>1× USB-B<br>Downstream:<br>2× USB-A |
| Webcam and microphone | – | – | – | ◆ | – | – | – | – | – | – | – | – | – | – | – | – | – |
| USB-C Power Delivery | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | – | – | – |
| Daisy Chaining | – | – | – | – | – | – | – | ◆ | ◆ | ◆ | – | – | – | – | – | – | – |
| LAN port | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | ◆ | – | – | – | – | – | – | – |
| Stand | Two rigid arms<br>Rotation: 70°<br>Height: 60mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 70°<br>Height adjustment: 195mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 70°<br>Height adjustment: 192.7mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 90°<br>Height adjustment: 195mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 90°<br>Height adjustment: 195mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 90°<br>Height adjustment: 195mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 90°<br>Height adjustment: 195mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 176.6mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 182.2mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 191.2mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 169mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 169mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 182.2mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 191.2mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 129.5mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 140mm | Tilt range: 35° to the back 5° to the front<br>Rotation: 344°<br>Height adjustment: 140mm |
| Warranty | 5 Years | 7 Years | 5 Years | 5 Years | 7 Years | 5 Years | 5 Years | 5 Years | 5 Years | 5 Years | 7 Years | 7 Years | 5 Years | 5 Years | 7 Years | 7 Years | 5 Years |

**The n**
**and the**

**Optimal ergon**

- Height adj
- Auto EcoV
- Flicker-free
  control
- Matte anti-
- Narrow bo
- Ergonom

**Environmenta**

- Energy-s
- Product
- High-qu

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries.

All other product names are trademarks or registered trademarks of their respective owners.

Visit us: We offer free loan units for testing and technical support in both pre-sales and after-sales.

Find local sales partners or EIZO contact persons: **eizo.eu/contact**

Copyright © 2026 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany.
All rights, errors and modifications are subject to change. Last updated: June 2026

Working with the Best