

## Technical Data

### GENERATION & STANDARDS

|                              |                                                                                                                                                        |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification                | CE, FCC, CB, RoHS, TÜV-Ergonomics (including BS2093, EN 307), RCM, ENEC, FCC-B, CANICE-S3 (B), UL-W/S, VCCI-B, EPA ENERGY STAR, EPEAT, WEEE, RoHS, COC |
| Case color                   | Light gray                                                                                                                                             |
| Panel type & series          | Onyx                                                                                                                                                   |
| Other box contents           | Signal cable (DVI-D + DVI-D), Quick guide, User manual (viewable via download)                                                                         |
| Area of application          | Power and workstation companies, Private users                                                                                                         |
| Accessories                  | None                                                                                                                                                   |
| Specific system requirements | None                                                                                                                                                   |
| WARRANTY                     |                                                                                                                                                        |
| Warranty period              | 3 years for panel and LCD module (operation hours not limited)                                                                                         |

### SCREEN

|                         |      |
|-------------------------|------|
| Screen size (in inches) | 21.3 |
| Screen size (in cm)     | 54   |
| Format                  | 4:3  |

## 21" office monitor

|                                              |                                                            |
|----------------------------------------------|------------------------------------------------------------|
| Viewable image area (width x height) (in mm) | 452 x 324                                                  |
| Ideal and recommended resolution             | 1600 x 1200                                                |
| Pixel pitch (in mm)                          | 0.27 x 0.27                                                |
| Pixel density (in ppi)                       | 94                                                         |
| Supported resolutions                        | 1600 x 1200, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 480 |
| Panel technology                             | IPS                                                        |
| Max. viewing angle horizontal                | 178                                                        |
| Max. viewing angle vertical                  | 178                                                        |

- ✓ **4:3 format and IPS panel in compact and space-saving design**
- ✓ **Brightness 500 cd/sqm, contrast 1800:1, 178° viewing angle**
- ✓ **6 ms switching time gray-gray with overdrive function**

|                                                          |     |
|----------------------------------------------------------|-----|
| Response time grey-to-grey alternation (typical) (in ms) | 6   |
| Backlight                                                | LED |

### CONNECTIONS

|                      |                                                 |
|----------------------|-------------------------------------------------|
| Signal inputs        | D-Sub, DisplayPort (HDCP 1.3), DVI-D (HDCP 1.4) |
| USB specification    | USB 2                                           |
| USB upstream ports   | 1 x type B                                      |
| USB downstream ports | 2 x type A                                      |
| Graphic signal       | DVI Single Link (TMDS), RGB Analog, DisplayPort |
| Sync formats         | Separate                                        |

Find your EIZO contact  
EIZO Europe GmbH  
Belgrader Straße 2  
40699 Mönchengladbach  
Phone: +49 2161 8210 0  
[www.eizo.eu](http://www.eizo.eu)

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 40699 Mönchengladbach, Germany. All rights, errors and modifications reserved. Last update: 16.07.2024

### FEATURES & OPERATION

|                                    |                                                                                                                                                                                            |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Preset color/gray scale modes      | Personal memory locations, sRGB, Paper, Movie, sRGB, CM                                                                                                                                    |
| DICOM tone curve                   | ✓                                                                                                                                                                                          |
| Auto EcoView                       | ✓                                                                                                                                                                                          |
| EcoView Index                      | ✓                                                                                                                                                                                          |
| EcoView Optimizer                  | ✓                                                                                                                                                                                          |
| Overdrive                          | ✓                                                                                                                                                                                          |
| No flickering                      | ✓                                                                                                                                                                                          |
| HDCP Decoder                       | ✓                                                                                                                                                                                          |
| Automatic signal input recognition | ✓                                                                                                                                                                                          |
| On-screen menu languages           | de, en, fr, es, it, zh                                                                                                                                                                     |
| Adjustment options                 | Color Mode, Brightness, Contrast, Color temperature / White point, Gamma, Overdrive, Colour tone, Color saturation, Readout on, Scaling, OSD language, Signal Input, All EcoView functions |
| Integrated power unit              | ✓                                                                                                                                                                                          |

### ELECTRICAL DATA

|           |                                                                                             |
|-----------|---------------------------------------------------------------------------------------------|
| Frequency | Digital 31 - 76 kHz / 59 - 61 Hz; Analog 24 - 80 kHz / 49 - 76 Hz (1600 x 1200; 59 - 61 Hz) |
|-----------|---------------------------------------------------------------------------------------------|

|                                                    |                                                              |
|----------------------------------------------------|--------------------------------------------------------------|
| Power consumption with power switch on (in watts)  | 13                                                           |
| Maximum Power Consumption (in watts)               | 42 (at maximum brightness with all signal inputs and OSD on) |
| Max. Power consumption in standby mode (in watts)  | 0.5                                                          |
| Power consumption with power switch off (in watts) | 0                                                            |

- ✓ **Auto EcoView, EcoView Index and EcoView Optimizer for maximum energy savings and optimal ergonomics**
- ✓ **USB hub with one upstream and two downstream ports**
- ✓ **Power management**
- ✓ **DisplayPort, DVI-D and D-Sub input for digital and analog connection**

### SIZE & WEIGHT

|                                                             |                                         |
|-------------------------------------------------------------|-----------------------------------------|
| Dimensions (incl. stand) (width x height x depth) (in mm)   | 485 x 453 - 535 x 208.5                 |
| Weight (incl. stand) (in kg)                                | 8.1                                     |
| Dimensions (without stand) (width x height x depth) (in mm) | 485 x 361 x 64                          |
| Weight (without stand) (in kg)                              | 5.1                                     |
| Dimension drawing (PDF)                                     | <a href="#">Dimension drawing (PDF)</a> |
| Rotatability of the stand (in °)                            | 70                                      |
| Tiltability forwards/backwards (in °)                       | 0 / 40                                  |
| Pivot between portrait / landscape                          | clockwise                               |
| Height adjustment range (in mm)                             | 82                                      |
| Hole spacing                                                | 100 x 100                               |