



- Efficiency: Application Services On Demand
- Reliability: Maximum Uptime with Advanced Hardware
- Value: Lowest Cost Per Connection (CPS), Throughput and Session

### Application Delivery

- Accelerate with SSL Offload, RAM Caching and more
- Advanced features with GSLB, aFlex traffic control and aXAPI management
- Optimize any application, including Microsoft SharePoint, Exchange, Lync, ADFS, Oracle, DNS, and more
- Improve Web server response times and reduce required servers
- No feature licensing fees

### Security

- Web Application Firewall (WAF)
- DNS Application Firewall (DAF)
- Next-generation DDoS mitigation
- SSL Intercept (SI)
- Application Access Management (AAM) for pre-authentication

### Cost-Effective Scalability

- Application Delivery Partitions (ADPs) for virtualization and multi-tenancy
- Scale-up to 8x with Virtual Chassis (aVCS)
- 10 Gb port connectivity
- More processing power: Intel Xeon Quad-core CPU
- No performance licenses


### Built for Maximum Uptime

- 80 Plus “Platinum” efficiency Redundant Power Supplies
- SSD (no spinning media)
- Error Correcting Code (ECC) memory
- Hot swap smart fans
- Application health checks

A10 Thunder 3030S is a 64-bit 1U Unified Application Service Gateway that consolidates premium solution modules for intelligent cloud services in the most efficient form factor. Built on A10’s scalable and flexible Advanced Core Operating System (ACOS) architecture, A10 Thunder Series platforms consolidate stand-alone solutions such as Application Delivery Controllers (ADCs), Server Load Balancers (SLBs), Carrier Grade NAT (CGN/CGNAT), IPv6 Migration, DNS Application Firewall (DAF), Web Application Firewall (WAF), SSL Intercept (SI), Distributed Denial of Service (DDoS) protection, Application Access Management (AAM), and more, without licensing fees.

The A10 Thunder 3030S sets new industry efficiency standard delivering 750,000 Layer 4 connections per second (CPS) and 30 Gbps of application throughput in a 1U appliance. NITROX III SSL acceleration hardware delivers exceptional 2048-bit key performance with 14,000 SSL CPS. Advanced hardware such as 10 Gbps ports provide high-performance connectivity for premium value.

High-capacity and high-performance multi-tenancy with up to 64 Application Delivery Partitions (ADPs) deliver large-scale virtualization and consolidation to enable more applications and services on a single platform, reducing deployment time and cost.



# A10 Thunder 3030S Features

## Application Delivery

- Comprehensive IPv4/IPv6 Support
- Advanced Layer 4/Layer 7 Server Load Balancing
  - ◆ Fast HTTP, Full HTTP Proxy
  - ◆ High-performance, template-based Layer 7 switching with header/URL/domain manipulation
  - ◆ Comprehensive Layer 7 application persistence support
- Comprehensive load balancing methods
  - ◆ Round Robin, Least Connections, Weighted RR, Weighted LC, Fastest Response, & more
- aFlex – deep packet inspection and transformation for customizable, application-aware switching
- Advanced Health Monitoring
  - ◆ Comprehensive Protocol Support – ICMP, TCP, UDP, HTTP, HTTPS, FTP, RTSP, SMTP, POP3, SNMP, DNS, RADIUS, LDAP, & more
- TCL scriptable health check support
- High Availability – Active-Active, Active-Standby configurations
- SIP Load Balancing for VoIP
- STARTTLS support for Secure Email (POPS, SMTPS, IMAPS) & LDAPS
- Spam Filter Support – high-speed application of very large black/white lists
- Firewall Load Balancing (FWLB)
- Global Server Load Balancing (GSLB)
- Transparent Cache Switching (TCS)
- Link Load Balancing (LLB)
- Diameter AAA Load Balancing
- Database Load Balancing

## Application Acceleration

- HTTP Acceleration & Optimization
  - ◆ HTTP Connection Multiplexing

- ◆ HTTP Caching
- ◆ HTTP Compression

## Security

- Web Application Firewall (WAF)
- Next-generation DDoS protection
  - ◆ SYN Cookies
  - ◆ IP Anomaly Detection
  - ◆ L7 attack prevention
- Application Access Management (AAM)
- DNS Application Firewall (DAF)
- SSL Intercept (SI)
- SSL Acceleration
  - ◆ Hardware-based SSL Offload
  - ◆ Support for all TCP Protocols – SSL Termination, SSL Bridging (SSL Initiation)
  - ◆ TLS 1.2 and 4096-bit SSL key support
- SSL Session ID Reuse
- Connection Rate Limiting/Connection Limiting

## High Performance, Scalable Platform

- ACOS Operating System
  - ◆ Multi-core support
  - ◆ Linear Application Scaling
  - ◆ Linux on control plane
- ACOS on data plane

## Networking

- Integrated Layer 2/Layer 3
- Transparent Mode/Gateway Mode
- Routing – Static Routes, IS-IS (v4/v6), RIPv2/ng, OSPF v2/v3, BGP4+
- VLAN (802.1Q)
- Trunking (802.1AX), LACP
- Access Control Lists (ACLs)
- Traditional IPv4->IPv4 NAT/NAPT
- IPv6->IPv6 NAPT
- Jumbo Frame support

## IPv6 Migration/IPv4 Preservation

- Full native IPv6 management and feature support
- SLB-PT (Protocol Translation), SLB-64 (IPv4<->IPv6, IPv6<->IPv4)
- Application Level Gateways (ALGs) for FTP, TFTP, RTSP, PPTP, SIP, ICMP, DNS, ESP
- Carrier Grade NAT (CGNAT), Large Scale NAT (LSN), NAT444, NAT44, NAT46
- NAT64/DNS64, DS-Lite, 6rd

## Management

- Dedicated management interface (Console, SSH, Telnet, HTTPS)
- Web-based Graphical User Interface (GUI) with Language Localization
- Industry-standard Command Line Interface
- SNMP, Syslog, email alerts
- Port mirroring
- REST-style XML API (aXAPI)
- LDAP, TACACS+, RADIUS support

## Virtualization

- aVCS (Virtual Chassis System)
- SoftAX Virtual Appliance (separate)
- Multi-tenancy with Application Delivery Partitions (ADPs)
  - ◆ Role-based Administration (RBA)
  - ◆ Partition-based management
  - ◆ L2/L3 virtualization
- Hypervisor acceleration and management integration

## Carrier-grade Hardware

- Advanced hardware architecture
- Redundant Power Supplies
- AC or DC Power Supplies
- Smart Fans (hot swap)
- Solid-state drive (SSD)
- 10 Gb, 1 Gb Ports
- Lights Out Management (LOM/IPMI)

Thunder 3030S				
<b>Application Throughput</b>	30 Gbps	<b>SSL Acceleration ASIC</b>	Yes	
<b>Layer 4 CPS</b>	750k	<b>Power Consumption (Typical/Max)</b>	131 W / 139 W	
<b>SSL CPS (1024/2048)</b>	47k / 14k	<b>Heat in BTU/hour (Typical/Max)</b>	447 / 474	
<b>Application Delivery Partitions (ADP) RBA/L3V</b>	128 / 64	<b>Performance Per Watt (PPW)*</b>	5,396	
<b>Ethernet Interface</b>		<b>Power Supply (DC option available)</b>	Dual 600 W RPS	
1 Gb Copper	6		80 Plus "Platinum" efficiency, 100 to 240 VAC, Frequency 50 – 60 Hz	
1 Gb Fiber (SFP)	2			
1/10 Gb Fiber (SFP+)	4	<b>Cooling Fan</b>		Hot Swap Smart Fans
40 Gb Fiber (QSFP+)	0	<b>Dimensions</b>		1.75 in (H), 17.5 in (W), 17.45 in (D)
<b>Management Interface</b>	Yes	<b>Rack Units (Mountable)</b>	1 RU	
<b>Lights Out Management</b>	Yes	<b>Unit Weight</b>	20.1 lbs	
<b>Console Port</b>	Yes	<b>Operating Ranges</b>	Temperature and Humidity 0° - 40° C / 5% - 95%	
<b>Solid-state Drive (SSD)</b>	Yes	<b>Regulatory Certifications</b>	FCC Class A, UL, CE, TUV, CB, VCCI   China CCC,BSMI, RCM (replace C-Tick), GOST-R, FAC	
<b>Processor</b>	Intel Xeon Quad-core	<b>Standard Warranty</b>	90-day Hardware & Software	
<b>Memory (ECC RAM)</b>	16 GB			

\* Layer 4 CPS per Watt (Max)